

**DEVELOP**

Dynamic balance

[www.develop.eu](http://www.develop.eu)



# ineo+ 3350i

- > Colour A4 multifunctional
- > Up to 33 ppm

## Option diagram






1 Enhanced Features
PDF enhancements LK-102v3
OCR text recognition LK-105v4
Barcode fonts LK-106
Unicode fonts LK-107
OCR A and B fonts LK-108
Document converter pack LK-110v2
ThinPrint® client LK-111
Serverless pull printing LK-114
Trusted Platform Module activation LK-115v2
Antivirus LK-116

2 Connectivity	
Fax board FK-517	x2
Wireless LAN UK-221	
USB I/F kit EK-P08	OR
USB I/F kit EK-P09	
I/F cable for CSRC modem EK-P11	
Biometric authentication AU-102	OR
ID card reader	
Mount kit MK-P08	

3 Others
Working table WT-P03
Double feed detection kit UK-P19
10-Key pad KP-102
Keyboard holder KH-P02
Air cleaning unit CU-202
Mount kit MK-P09

4 Media Input	
Paper tray PF-P20	x2
Height adjustment unit PF-P22	
Copier desk DK-P04x	

5 Media output
Off-line stapler FS-P04

legend
 Mandatory option
 Option
 This option can only be installed with the respective option above it

## Finishing functionalities



Duplex



Corner stapling

## Description

### Enhanced Features

<b>LK-102v3 PDF Enhancements</b>	PDF/A (1b); PDF encryption; digital signature
<b>LK-105v4 OCR text recognition</b>	Searchable PDF and PPTX
<b>LK-106 Barcode fonts</b>	Supports native barcode printing
<b>LK-107 Unicode fonts</b>	Supports native Unicode printing
<b>LK-108 OCR A and B fonts</b>	Supports native OCR A and B font printing
<b>LK-110v2</b>	Generates various file formats
<b>Document converter pack</b>	incl. DOCX, XLSX and PDF/A
<b>LK-111 ThinPrint® client</b>	Print data compression for reduced network impact
<b>LK-114 Serverless Pull Printing</b>	Secure and Follow Me printing solution requiring no server application
<b>LK-115v2 Trusted Platform Module</b>	Trusted Platform Module for protection of data encryption and decryption
<b>LK-116 Antivirus</b>	Bitdefender® antivirus provides real time scanning of all incoming and outgoing data

### Connectivity

<b>FK-517 Fax board</b>	Super G3 fax, digital fax functionality
<b>UK-221 Wireless LAN</b>	Wireless LAN and wireless LAN Access Point Mode
<b>EK-P08 USB I/F kit</b>	USB keyboard connection
<b>EK-P09 USB I/F kit</b>	USB keyboard connection; Bluetooth
<b>EK-P11 I/F cable for CSRC modem</b>	GPRS modem connection for CSRC
<b>AU-102 Biometric authenticaton</b>	Finger vein scanner
<b>ID card reader</b>	Various ID card technologies
<b>MK-P08 Mount kit</b>	Installation kit for ID card reader

### Others

<b>WT-P03 Working table</b>	Authentication device placement
<b>UK-P19 Double feed detection kit</b>	Multi-feed detector to reduce errors and paper jams
<b>KP-102 10-Key pad</b>	For use instead of touchscreen
<b>KH-P02 Keyboard holder</b>	To place USB keyboard
<b>CU-202 Air cleaning unit</b>	Improving indoor air quality by reduced emissions
<b>MK-P09 Mount kit</b>	Installation kit for Air cleaning unit

### Media Input

<b>PF-P20 Paper tray</b>	500 sheets, A4, 60-90 g/m <sup>2</sup>
<b>PF-P22 Height adjustment unit</b>	To achieve comfortable height for operation
<b>DK-P04x Copier desk</b>	Provides storage space for print media and other materials

### Media output

<b>FS-P04 Off-line stapler</b>	20-sheet off-line stapling
--------------------------------	----------------------------

## Technical specifications

### SYSTEM SPECIFICATIONS

<b>Panel size/resolution</b>	10.1" / 1024 x 600
<b>System memory (standard/max)</b>	5,120 MB
<b>System hard drive</b>	256 GB SSD (standard)
<b>Interface</b>	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n (optional)
<b>Network protocols</b>	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S); AppleTalk; Bonjour
<b>Automatic document feeder (standard)</b>	Up to 80 originals; A5–A4; 50–128 g/m <sup>2</sup> ; Dualscan ADF
<b>Paper input capacity (standard/max)</b>	600 sheets / 1,600 sheets
<b>Paper tray input (standard)</b>	1x 500 sheets; A6–A4; custom sizes; 60–210 g/m <sup>2</sup>
<b>Paper tray input (optional)</b>	1x 500 sheets; A4 ;60–90 g/m <sup>2</sup> 1x 500 sheets; A4 ;60–90 g/m <sup>2</sup>
<b>Manual bypass</b>	100 sheets; A6–A4; Custom sizes; 60–210 g/m <sup>2</sup>
<b>Automatic duplexing</b>	A4; 60–210 g/m <sup>2</sup>
<b>Finishing modes (optional)</b>	Group; Sort; Staple (offline)
<b>Output capacity (standard)</b>	Max. 250 sheets
<b>Copy/print volume (monthly)</b>	Rec. 6,500 pages; Max. <sup>1</sup> 96,000 pages
<b>Toner lifetime</b>	Black up to 13,000 pages CMY up to 9,000 pages
<b>Imaging unit lifetime</b>	Black up to 159,000 pages (imaging unit) CMY up to 55,000 pages (imaging unit)
<b>Power consumption</b>	220–240 V / 50/60 Hz; Less than 1.45 kW
<b>System dimension (W x D x H)</b>	420 x 528 x 572 mm (without options)
<b>System weight</b>	Approx. 39.0 kg (without options)

### PRINTER SPECIFICATIONS

<b>Print resolution</b>	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
<b>Page description language</b>	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
<b>Operating System</b>	Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Macintosh OS X 10.10 or later; Unix; Linux; Citrix
<b>Printer fonts</b>	80 PCL Latin; 137 PostScript 3 Emulation Latin
<b>Mobile printing</b>	AirPrint (iOS); Mopria (Android); Mobile Authentication and Pairing (iOS/Android) Optional: Google Cloud Print; WiFi Direct

### SCANNER SPECIFICATIONS

<b>Scan speed (mono/colour)</b>	Up to 45/45 ipm in simplex Up to 90/90 ipm in duplex
<b>Scan modes</b>	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-to-URL; TWAIN scan
<b>File formats</b>	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact XPS; PPTX // Optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/PPTX/XLSX
<b>Scan destinations</b>	2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	HD polymerised toner
Copy/print speed A4 (mono/colour)	Up to 33/33 ppm
Autoduplex Speed A4 (mono/colour)	Up to 33/33 ppm
1st copy out time A4	5.6/6.3 sec.
Warm-up time	Approx. 13 sec. in mono; 15 sec. in color <sup>2</sup>
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	A6–A4; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

SYSTEM FEATURES

Security Functions (standard)	ISO 15408 HCD-PP Common Criteria (in evaluation); IP filtering and port blocking; SSL2; SSL3 and TLS1.0/1.1/1.2 network communication; IPsec support; IEEE 802.1x support; User authentication; Authentication log; Secure print; Kerberos; Hard drive overwrite; Hard drive data encryption (AES 256); Memory data auto deletion; Confidential fax receipt; Print user data encryption
Security Functions (optional)	Antivirus realtime scanning (Bitdefender®)
Accounting (standard)	Up to 1,000 user accounts; Active Directory support (user name + password + e-mail + smb folder); User function access definition
Accounting Functions (optional)	Biometric authentication (finger vein scanner); ID card authentication (ID card reader); Authentication by mobile device (Android/iOS)
Software	store+find (opt.); convert+share (opt.); Device Manager; Box Operator; Data Administrator (user accounts & cost centres); Card solutions (opt.); EveryonePrint (opt.)

<sup>1</sup> If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

<sup>2</sup> Warm-up time may vary depending on the operating environment and usage



DEVELOP

Konica Minolta Business Solutions Europe GmbH  
 Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu

- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.